



TECHNISCHE
UNIVERSITÄT
WIEN



NB 1746

Prüflabor für Feuerungsanlagen

am Institut für Verfahrenstechnik,
Umwelttechnik und Technische
Biowissenschaften

Getreidemarkt 9/166
A-1060 Wien

Email: prueflabor@tuwien.ac.at

Tel.: ++43 1 58801 /166888
Fax: ++43 1 58801 /15999

Test Certificate

Manufacturer	ThermoFLUX d.o.o. Bage 3 70101 Jajce Bosnia and Hercegovina
Client	Firevision Austria GmbH Gewerbestrasse 1/2 5325 Plainfeld Austria
Type of test	Initial testing in accordance with the requirements of EN 303-5
Name of device	Ecologic plus 15
Name of the tested model	LOGIC 15
Testing Fuel	Wood pellets (EN plus A1)
Nominal heat output kW	17,5
Partial heat output in kW	5,6
Test reports for the evaluation	PL-20022-1-P from 09.02.2021 of the Test Laboratory for Combustion Plants at the Institute of Chemical, Environmental & Bioscience Engineering at the Vienna University of Technology.

Assessment:

Based on the testing carried out, the requirements related to EN 303-5, to the agreement pursuant to Article 15a of the Federal Constitution Act on the "Marketing of residential heating and inspection of combustion plants and cogeneration units" as well as to regulation (EU) 2015/1187 and to regulation (EU) 2015/1189 are met.

Test results and limit values	Appendix (2 pages)
-------------------------------	--------------------

Vienna, 01.03.2022

Person responsible for testing

Dipl.-Ing. S. Diem



INSTITUT FÜR VERFAHRENSTECHNIK,
UMWELTECHNIK UND
TECHNISCHE BIOWISSENSCHAFTEN
A-1060 WIEN, GETREIDEMARKT 9/166

Head of Laboratory

Dipl.-Ing. Dr. S. Müller

The context of this test certificate may only be reproduced literally and according to form in case of copy and publication.

Appendix to Test Certificate for boiler “Ecologic plus 15“

Date of testing		17.11.2020	04.08.2020
Test run		Full load	Partial load
Test results			
Test period	min	367	365
Fuel quantity	kg	24,5	7,8
Fuel power	kW	19,2	6,1
Fuel conversion	kg/h	4,0	1,3
Mean draught	Pa	11,9	11,5
Barometric pressure	mbar	1007,7	1009,9
Atmospheric humidity	%	31,3	47,9
Room temperature	°C	27,0	26,8
Mean flue gas temperature	°C	130,9	58,4
Flue gas mass flow rate	g/s	9,1	4,6
Boiler efficiency (direct)	%	91,3	91,0
Heat output (direct)	kW	17,5	5,6
Mean of O ₂	Vol%	6,4	11,5
Mean of CO ₂	Vol%	14,0	9,0
Mean of CO	ppm	43	131
Mean of NO	ppm	101	63
Mean of HC (Org. C)	ppm	3	1
Mean of PM ¹	mg/m ³	10	10

		Emissions (under standard conditions at 0 °C and 1013 mbar)		
		mg/m ³ at 10 % O ₂	mg/m ³ at 13 % O ₂	mg/MJ
		CO	Full load	40
	Partial load	189	137	89
NO as NO ₂	Full load	156	114	74
	Partial load	149	108	70
OGC (Org. C)	Full load	4	3	<3
	Partial load	<3	<3	<3
PM ¹	Full load	8	6	4
	Partial load	11	8	5

¹Average of four single measurements where at all are lower than the limit value.

	Seasonal space heating emissions (under standard conditions at 0 °C and 1013 mbar)
	mg/m ³ at 10 % O ₂
CO	167
NO as NO ₂	150
OGC	2
PM	11

The test results relate only to the test objects at the time of testing.

Appendix to Test Certificate for boiler “Ecologic plus 15“

Seasonal space heating energy efficiency (η_s)	81
Energy Efficiency Index (EEI)	118
Energy Efficiency Class	A+

Limit values	EN 303-5		Art. 15a B-VG	
	Full load	Partial load	Full load	Partial load
Efficiency %	≥ 88,2		≥ 81,9	
Emissions	mg/m ³ at 10% O ₂		mg/MJ	
CO	500		250	
NO as NO ₂	-		100	
OGC	20		20	
PM	40		20	

Limit values	Regulation (EU) 2015/1189
Seasonal space heating energy efficiency %	≥ 75 / ≥ 77*
Seasonal space heating emissions	mg/m ³ at 10% O ₂
CO	500
NO as NO ₂	200
OGC	20
PM	40

*at nominal heat output > 20 kW

Energy Efficiency Class	EEI
A+++	≥ 150
A++	≥ 125
A+	≥ 98
A	≥ 90
B	≥ 82
C	≥ 75
D	≥ 36
E	≥ 34
F	≥ 30
G	< 30